

PM-613 GOLDENFLOK

COAGULANT

PM-613 GOLDENFLOK is a product based on organic polymers that removes fat, sun oils, organic matter, pollen, etc. from the surface of water by coagulation and subsequent removal by filtration. By this way they don't deposit in the bottom of the pool. The product also acts as a brightener in maintenance treatments.

APPLICATIONS:

- Shock treatments in green pools with turbidity.
- Maintenance treatments.
- Industrial procedures.



METHOD OF USE AND DOSAGE:

- Wash the filter before the application of the product.
- Spread throughout the whole swimming pool. Filter for 4 to 8 hours. Wash the filter when the manometer indicates it.
- Cloudy water: 0.25 L/100 m³ every 24 hours until it becomes clear.
- Maintenance: 0.15 L/100 m³ every week or every 15 days, depending on the bath load.

PHYSICAL PROPERTIES:

- Appearance: Colourless to pale yellow liquid
- Odour: Odourless
- pH: 4.0 – 5.0
- Density: 1.051 – 1.076 g/cm³
- Solubility in water: Miscible in water in all proportions

PRECAUTIONARY STATEMENTS:

- Keep out of reach of children.
- Do not get in eyes, on skin, or on clothing.
- Call a poison centre or doctor/physician if you feel unwell.

PACKAGING:

0.5, 1, 5, 20 L bottles